

PRECEDING PAGE BLANK NOT FILMED

SLEWING AND VIBRATION CONTROL
OF
THE SCOLE

JIGUAN GENE LIN

CONTROL RESEARCH CORPORATION
LEXINGTON, MA 02175

I. INTRODUCTION

II. STRUCTURAL VIBRATIONS IN SCOLE EXCITED BY
TIME-MINIMIZED RAPID SLEWING

-- BANG-PAUSE-BANG (BPB) CONTROL (800 LB)

-- BANG-BANG (BB) CONTROL (0, 80, 25 LBS)

HOW BAD? ALWAYS THAT BAD?

NO FORCE MEANS LEAST EXCITATION?

III. ACTIVE DAMPING OF BPB-EXCITED VIBRATIONS
USING HIGH-PERFORMANCE MODAL DASHPOTS

DIRECT VELOCITY OUTPUT FEEDBACK REALLY CANNOT
CONTROL EXCESSIVE VIBRATIONS EFFECTIVELY, QUICKLY?

IV. COMMENTS

V. CONCLUSIONS

VI. RECOMMENDATIONS

- SCOLE PRIMARY CONTROL TASK IS:
RAPIDLY SLEW OR CHANGE THE LINE-OF-SIGHT (LOS), AND
SETTLE OR DAMP STRUCTURAL VIBRATIONS TO A REQUIRED DEGREE

- THE OBJECTIVE IS:
MINIMIZE THE TIME REQUIRED TO SLEW AND SETTLE,
UNTIL LOS REMAINS WITHIN A SPECIFIED ANGLE.

- 2-STAGE APPROACH:
FIRST: SLEW THE WHOLE STRUCTURE LIKE A RIGID BODY,
-- IN A MINIMUM TIME,
-- UNDER THE LIMITED CONTROL MOMENTS AND FORCES
THEN: DAMP THE EXCITED STRUCTURAL VIBRATIONS

- SOME PREVIOUS RESULTS ON STAGE-1 DESIGN

CASE	STRATEGY (LB-FT)	MOMENT (LB)	FORCE (DEG)	LOS ERROR (SEC)	SLEW TIME
F10	BB	10,000	0	.150	12.604
→ F11	BPB	10,000	800	.086	4.892 ←
F12	BB	10,000	800	.097	3.756

- OBJECTIVE OF CURRENT STUDY
STAGE-2 DESIGN: ACTIVE CONTROL OF EXCITED VIBRATIONS

STRUCTURAL VIBRATIONS EXCITED BY
BANG-BANG-TYPE RAPID SLEW MANEUVERS

FORCE (LB)	MOMENT (LB-FT)	STRATEGY (SEC)	SLEW TIME (SEC)	LOS ERROR (DEG)	DEFLECT. (FT)	ATT. DEV. (DEG)
800	10,000	.267 (B)	4.892 (NOTE 1)	89.8	+114	+88.35
		3.158 (P)		OR	-113	-86.96
		.867(-B)		133.3		
0	SAME	6.307 (B)	12.614	6.25	+5.06	+3.83
		6.307(-B)			-5.18	-4.02
80	SAME	4.416 (B)	8.832	24.7	+20.59	+15.98
		4.416(-B)			-10.83	-8.31
25	SAME	5.479 (B)	10.959	0.51	+0.25	+0.16
		5.479(-B)			-0.30	-0.30

NOTE 1. TIME OF APPLICATION IS 1.734 SEC, ONLY 35.32% OF THE SLEW TIME.




Fig. 3-1 Vibratory responses to Rapid Time-minimized Bang-Pause-Bang Slew;
 a. Line-of-sight error and Mast tip deflection.





Fig. 3-1 Vibratory responses to Rapid Time-minimized Bang-Pause-Bang Slew;
b. Attitude deviations at the Shuttle (S) and the Reflector (R) ends.





Fig. 3-2 Vibratory responses to Rapid Time-minimized Bang-Bang Slew: 0 lb;
a. Line-of-sight error and Mast tip deflection.





Fig. 3-2 Vibratory responses to Rapid Time-minimized Bang-Bang Slew: 0 lb;
b. Attitude deviations at the Shuttle (S) and the Reflector (R) ends.





Fig. 3-3 Vibratory responses to Rapid Time-minimized Bang-Bang Slew: 80 lb;
a. Line-of-sight error and Mast tip deflection.





Fig. 3-3 Vibratory responses to Rapid Time-minimized Bang-Bang Slew: 80 lb;
b. Attitude deviations at the Shuttle (S) and the Reflector (R) ends.





Fig. 3-4 Vibratory responses to Rapid Time-minimized Bang-Bang Slew: 25 lb;
a. Line-of-sight error and Mast tip deflection.





Fig. 3-4 Vibratory responses to Rapid Time-minimized Bang-Bang Slew: 25 lb;
b. Attitude deviations at the Shuttle (S) and the Reflector (R) ends.

- USING NO FORCES ON REFLECTOR DOES NOT MEAN LEAST EXCITATION!
- IF LOS ERROR IS THE ONLY CONCERN, STOP USING 800LB FORCE;
USE 25LB (VERNIER THRUSTER LEVEL) INSTEAD.
-- BUT TIME IS EQUALLY IMPORTANT!!!
- ADDITIONAL TIME OF VARIOUS LENGTH IS STILL REQUIRED
FOR DAMPING OUT THE EXCITED VIBRATIONS.
- VIBRATION CONTROL CHALLENGE:
CAN EXCESSIVE VIBRATIONS,
SUCH AS EXCITED BY THE 800LB RAPID SLEWING,
BE EFFECTIVELY SUPPRESSED TO A REASONABLE LEVEL
QUICKLY, SAY, IN 5 SEC?

MODAL-DASHPOT DESIGN MD1

PART 1: LINEAR VELOCITY FEEDBACK

$$\begin{bmatrix} U_7 \\ U_8 \end{bmatrix} = - G_{LVR} \begin{bmatrix} Y_{15} \\ Y_{16} \end{bmatrix}$$

$$\begin{bmatrix} U_7 \\ U_8 \end{bmatrix} = F_4 = \begin{bmatrix} \text{APPLIED FORCE ON REFLECTOR IN X-DIRECTION} \\ \text{APPLIED FORCE ON REFLECTOR IN Y-DIRECTION} \end{bmatrix}$$

$$\begin{bmatrix} Y_{15} \\ Y_{16} \end{bmatrix} = \begin{bmatrix} \text{RATE OF XZ-DEFLECTION AT REFLECTOR END} \\ \text{RATE OF YZ-DEFLECTION AT REFLECTOR END} \end{bmatrix}$$

$$G_{LVR} = \begin{bmatrix} .58420630E+01 & .43392044E+00 \\ .42038249E+00 & .69796355E+01 \end{bmatrix}$$

ADDITIONAL DAMPING RATIO DESIGNED = 0.6737, Mode 2
 = 0.6, Mode 1

2% SETTLING TIME OF 3 SEC IS DESIGNED FOR MODE 2

MODAL-DASHPOT DESIGN MD1

PART 2: ANGULAR VELOCITY FEEDBACK

$$\begin{bmatrix} U_4 \\ U_5 \\ U_6 \end{bmatrix} = - G_{AVR} \begin{bmatrix} Y_{10} \\ Y_{11} \\ Y_{12} \end{bmatrix}$$

$$\begin{bmatrix} U_4 \\ U_5 \\ U_6 \end{bmatrix} = M_4 = \begin{bmatrix} \text{APPLIED MOMENT ON REFLECTOR ABOUT X-AXIS} \\ \text{APPLIED MOMENT ON REFLECTOR ABOUT Y-AXIS} \\ \text{APPLIED MOMENT ON REFLECTOR ABOUT Z-AXIS} \end{bmatrix}$$

$$\begin{bmatrix} Y_{10} \\ Y_{11} \\ Y_{12} \end{bmatrix} = \begin{bmatrix} \text{RATE OF REFLECTOR ROLL ATTITUDE DEVIATION} \\ \text{RATE OF REFLECTOR PITCH ATTITUDE DEVIATION} \\ \text{RATE OF REFLECTOR YAW ATTITUDE DEVIATION} \end{bmatrix}$$

$$G_{AVR} = \begin{bmatrix} .24172707E+04 & .16653096E+03 & .45158162E+03 \\ .15734103E+03 & .21781213E+04 & -.72768193E+03 \\ .13433660E+04 & -.22055215E+04 & .42951681E+04 \end{bmatrix}$$

ADDITIONAL DAMPING RATIO DESIGNED = 0.03, MODES 3,4,5

INHERENT DAMPING RATIO ASSUMED = 0.003 ALL MODES





Fig. 6-1 Simulation results of vibration control design MD1;
 a. Histories of applied moments and forces at the Reflector.





Fig. 6-1 Simulation results of vibration control design MD1;
b. Histories of line-of-sight error and Mast tip deflection.





Fig. 6-1 Simulation results of vibration control design MD1;
c. Histories of attitude deviations at Shuttle (S) and Reflector (R) ends

ORIGINAL PAGE IS
OF POOR QUALITY





Fig. 6-1 Simulation results of vibration control design MD1;
d. Histories of normal coordinates of the 10 modes.

SI 1977-01-10
YALCOP 21 10 70

SUMMARY -- MD1

LOS ERROR < 18.46^0 $T = 2.5$ SEC
 < 17.46^0 $T > 2.5$ SEC
 $\cong 11.79^0$ $T = 3.1$ SEC

DEFLECTION $\leq \pm 5$ FT $T \cong 2$ SEC
 $\leq \pm 0.5$ FT $T = 4.2$ SEC

2% SETTling TIME ≤ 2.9 SEC

LAST PEAK REFLECTOR ATTITUDE DEVIATION:

ROLL $\cong 0.460^0$

PITCH $\cong 0.546^0$

YAW $\cong 1.360^0$

SUMMARY -- MD1A

ADDITIONAL DAMPING RATIO RE-DESIGNED = 0.6, Mode 2
CORRESPONDING 2% SETTling TIME FOR MODE 2 IS 3.38 SEC

$$G_{LVR} = \begin{bmatrix} .58420557E+01 & .45784262E+00 \\ .42061494E+00 & .62209375E+01 \end{bmatrix}$$

LOS ERROR $\leq 16.66^{\circ}$ (↓) $T \geq 1.8$ SEC

$\dot{=} 9.57^{\circ}$ (↓) $T = 3.1$ SEC

DEFLECTION $\leq \pm 7.35$ FT (↑) $T = 1.3$ SEC

$\leq \pm 0.75$ FT (↑) $T = 3.7$ SEC

2% SETTling TIME $\dot{=} 3$ SEC

LAST PEAK REFLECTOR ATTITUDE DEVIATION:

ROLL $\dot{=} 0.714^{\circ}$ (↑)

PITCH $\dot{=} 0.582^{\circ}$

YAW $\dot{=} 1.399^{\circ}$

COMMENTS

- THE MODAL DASHPOT DESIGN MET THE VIBRATION CONTROL CHALLENGE
FAIRLY WELL: EFFECTIVE, FAST SUPPRESSION OF EXCESSIVE VIBRATIONS
- FOR COMPLETE SUPPRESSION AND PRECISION POINTING
AFTER THE QUICK SUPPRESSION,
EITHER: INCREASE THE MODAL DASHPOT FEEDBACK GAINS
OR: SWITCH TO INTEGRATED DESIGN OF LQG/LTR AND MODAL DASHPOTS
- DIRECT VELOCITY OUTPUT FEEDBACK CONTROLLERS
NEED NOT BE OF "LOW AUTHORITY", LOW PERFORMANCE.
-- ADDITIONAL DAMPING RATIO CAN BE DESIGNED TO BE AS HIGH
AS TO THE OPTIMAL VALUE 0.707, IF NECESSARY;
INSTEAD OF RESTRICTING TO ONLY ABOUT 0.1
- NO MORE HIGH-GAIN PROBLEMS OF ORIGINAL CANAVIN DESIGN
- SPILLOVER IS MINIMAL: PERFORMANCE DEGRADATION UN-NOTICEABLE
SPILLOVER IS BENEFICIAL: CONCOMITANT ACTIVE DAMPING OF UNMODELED
MODES
- SYSTEMATIC DESIGN METHOD FOR MODAL DASHPOTS WORKS!

CONCLUSIONS

- 2-STAGE APPROACH IS FEASIBLE AND PROMISING FOR RAPID SLEWING AND PRECISION POINTING OF SCOPE
- NOT ALL BANG-BANG TYPE OF TIME-MINIMIZED SLEW MANEUVERS WILL EXCITE LARGE STRUCTURAL VIBRATIONS IN SCOPE
- MODAL DASHPOTS CAN BE A CONCENTRATED HIGH-POWER VIBRATION CONTROL, AS WELL AS THE USUAL DIFFUSE ("BROAD-BAND"), LOW-POWER ("LOW-AUTHORITY") CONTROL

RECOMMENDATIONS

- LIMIT THE MAGNITUDE OF APPLIED FORCES ON REFLECTOR TO EITHER 25 LB
 - LEVEL OF VERNIER THRUSTERS ON THE REAL SPACE SHUTTLEOR 150 LB
 - LEVEL EQUIVALENT TO THE COLD-GAS JETS OF LABORATORY SCOPE
- TO COMPLETE STAGE 2, ADD AN INTEGRATED DESIGN OF LQG/LTR (LINEAR-QUADRATIC-GAUSSIAN/LOOP-TRANSFER-RECOVERY) AND MODAL DASHPOTS
- VALIDATE THE 2-STAGE APPROACH USING THE SCOPE LABORATORY FACILITY WITH A COMPREHENSIVE SEQUENCE OF INTEGRATED DESIGNS AND EXPERIMENTS COUPLING NONLINEAR RIGID-BODY MOTIONS WITH FLEXIBLE-BODY DYNAMICS

